	CITY OF	
	<u></u>	
1		
4		-5
0	TTAWA	Z

Please Return Copy to:
City of Ottawa Water Treatment Plant
Po Box 60

Backflow Prevention Assembly Test Report

or email: backflow@ottawaks.gov

Reduced Pressure Principle Assembly Double Check Valve Assembly Double Check Valve Assembly Check Valve #1 Check Valve #2 Relief Valve Held atPSID Closed Tight cb Leaked cb Cleaned cb Replaced cb Re		CAWA	Ollawa, KS 00007								
Customer Name/Address: Prevents Backflow from: Typ Boiler	KA	NSAS	WHITE: Water Plant YELLOW: Tester PINK: Customer								
Customer Name/Address: Prevents Backflow from:	Manufact	turer:	Model:		Size:		Serial N	lumber:			
Prevents Backflow from: Boiler cb Ref Reduced Pressure Principle Assemply Double Check Valve #1							Location	n:			
Reduced Pressure Principle Assemply Double Check Valve #1 Check Valve #2 Relief Valve Held atPSID Closed Tight	Customer Name/Address:										
Reduced Pressure Principle Assembly Double Check Valve Assembly Use 2 Columns Check Valve #1 Check Valve #2 Relief Valve Fire Protection cb Held atPSID Held atPSID Closed Tight cb Leaked cb Cleaned cb Cleaned cb Replaced Replaced cb Repla						Prevents	Backflow from:		Type		
Double Check Valve #1							Boiler		cb	RP	
Check Valve #1	Reduced	Pressure P	rinciple A	ssemply					cb		
Held atPSID	Double C	heck Valve	Assembly	Use 2 Columns	Use 3	columns	Domesti	ic Usage	cb		
Closed Tight cb Leaked cb Closed Tight cb Leaked cb Cleaned cb Cleaned cb Replaced cb Replaced cb Replaced Give details of repair below Give details of repair below Give details of repair below Cleaned cb Replaced cb Replaced Cleaned Cleaned cb Cleaned ccb Replaced Give details of repair below Give details of repair below Cleaned ccb Replaced Test Result PSID PSID PSID PSID Closed Tight cb Opened at PSID Closed Tight cb Opened at Signature PSID PSID Closed Tight cb Opened at Signature PSID PSID PSID Closed Tight cb Opened at Signature PSID PSID PSID Closed Tight cb Opened at Signature PSID Signature PSID Closed Tight cb Opened at Signature PSID	Check '	Valve #1	Check	Valve #2	Relie	f Valve	Fire Pro	tection	cb		
Cleaned cb Cleaned cb Cleaned cb Replaced cb Replaced cb Replaced cb Replaced Give details of repair below Give details of repair below Cleaned cb Replaced Cleaned cb Replaced Give details of repair below Give details of repair below Cleaned cb Replaced Cleaned cb Replaced Cleaned cb Replaced Cleaned cb Replaced Replaced AFTER REPAIR Opened at PSID PSID Test Result Held atPSID PSID Test Result Held atPSID Closed Tight cb Opened at PSID Fail cb Differential pressure gauge used: Potable: cb Non-Potable: cb Non-Potable: cb Non-Potable: cb Non-Potable: cb Non-Potable: cb	Held at	PSID	Held at	PSID	Opened at_	PSID	Lawn Ir	rigation	cb		
Leaked cb Cleaned cb Cleaned cb Cleaned cb Replaced cc Cleaned cb Replaced cc Replaced cb Replaced cb Replaced cb Replaced cb Replaced cc	Closed Tig	ght cb	Closed Ti	8	Did Not C	pen	Other, E	Explain			
cb Replaced cb Replaced cb Replaced Give details of repair below Give details of repair below Give details of repair below Cb Replaced Give details of repair below Cb Cleaned cb Replaced cb Replaced Cleaned cb Replaced Replaced AFTER REPAIR Opened at PSID PSID Test Result Held atPSID Held atPSID Held atPSID Differential pressure gauge used: Potable: cb Non-Potable: cb Non-Potable: cb Last Claibration:		cb		cb			<u> </u>	•			
Give details of repair below Give details of repair below Give details of repair below Opened at									PVB/SVE		
PSID Cb Cleaned Cleaned Ccb Replaced Replaced AFTER REPAIR Opened at PSID PSID AFTER REPAIR Opened at PSID PSID Test Result Held at PSID Closed Tight cb Opened at PSID Differential pressure gauge used: Potable: Cb Non-Potable: Cb Non-Potable: Cb Non-Potable: Cb Non-Potable: Cb Non-Potable: Cb		-		-		-	AI	R INLET		CHECK VALVE	
cb Cleaned Cleaned cb Replaced AFTER REPAIR AFTER REPAIR Opened at PSID Test Result Held at PSID Held at PSID Closed Tight cb Opened at PSID Potable: cb Non-Potable: cb Make/Model Cleaned Cleaned Replaced Replaced AFTER REPAIR Opened at PSID PSID Test Result Pass cb Fail cb Non-Potable: cb Non-Potable: cb	Give details	of repair below	Give details	of repair below	Give details	of repair below	-			Held at	
cb Replaced AFTER REPAIR Opened at PSID Test Result Held at PSID Held at PSID Closed Tight cb Opened at PSID Differential pressure gauge used: Potable: cb Non-Potable: cb Non-Potable: cb Non-Potable: cb											
AFTER REPAIR Opened at PSID Test Result Pass cb Fail cb Differential pressure gauge used: Potable: Cb Non-Potable: Cb											
Opened at PSID							cb	Replaced		Replaced	
PSID PSID PSID PSID Test Result Pass cb Pass cb Fail cb Differential pressure gauge used: Make/Model PSID PSID PSID PSID Potable: cb Non-Potable: cb							AFTI	ER REPAIR] [AFTER REPAIR	
PSID PSID PSID PSID Test Result Pass cb Pass cb Fail cb Differential pressure gauge used: Make/Model PSID PSID PSID PSID Potable: cb Non-Potable: cb							Open	ed at		Held at	
Held atPSID							-				
Held at PSID Closed Tight cb Opened at PSID Fail cb Differential pressure gauge used: Potable: cb Non-Potable: cb Make/Model SN: Last Claibration:							Tes	t Result			
Held at PSID Closed Tight cb Opened at PSID Fail cb Differential pressure gauge used: Potable: cb Non-Potable: cb Make/Model SN: Last Claibration:			Held at	PSID			Pass	cb			
Make/Model SN: Last Claibration:	Held at	PSID			Opened at_	PSID					
T (D)	Differential pressure gauge used:				Potable:	cb	Non-Po	table: cb			
Remarks: Test Date:					Last Claibration:						
	Remarks:					Test Date:					
Company Name: Certified Tester Name (Print/Type)	Company Name: Certified T					Cester Name (Print/Type)					
Company Address: Certified Tester Signature	Company Address: Certified T					Cester Signature					
Company Phone # Certification # Expires:	Company Phone # Certificati					on # Expires:					